FORD TRUCKS 2533 LR EURO6





| Basic reactives | |
|-----------------|----------------------|
| Vehicle Type | Road Truck |
| Axle | 6x2 |
| Emission | Euro 6 |
| Cabin Type | Low Roof Sleeper Cab |
| Wheelbase (mm) | 4750 |

| Engine | |
|--------------------|----------------------------|
| Туре | Ecotorq 9 liters |
| Displacement (cc) | 8974 |
| Diameter x Stroke | 115 mm x 144 mm |
| Power | 330 PS (243 kW) @ 1900 rpm |
| Torque | 1300 Nm @ 1200-1700 rpm |
| Compression Ratio | 17,6 : 1 |
| Oil Filling Volume | 301 |

| Coolant Volume | 35 L |
|----------------|--------------------|
| Transmission | |
| Clutch | 430 mm Single Disc |

Manuel Transmission / Ratios (1.gear - 9. gear)

Steering

Power Assisted Single Circuit

9+1 Speed (9,48 - 0,75)

| Chassis | | | |
|--|--|--|--|
| Chassis Thickness | 7 mm with Reinforcement | | |
| Chassis Strength | 355 MPa | | |
| Suspension (Front/Rear) | Parabolic Leaf Spring / Compensating Arm Mechanical Suspension | | |
| Axle | Standard Single Reduction | | |
| Axle Ratio | 4,63 | | |
| Tyres (Front/Rear) | 315/80 R 22,5 | | |
| Wheel Rim | 22,5 x 9 Steel | | |
| Braking System | | | |
| Brakes (Front/Pear) (//mm y mm length) | 430 v 45 mm - Disc Brake | | |

| Electrical System | | | | |
|--|---|--|--|--|
| Engine Brake Power | max. 220 kW (Engine Level) | | | |
| Braking System | Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater | | | |
| Brakes (Front/Rear) (Ø.mm x mm. Llength) | 430 x 45 mm - Disc Brake | | | |

| Battery | 24V, 2 x 12V 150 Ah |
|----------------------------|---------------------|
| Alternator / Starter Motor | 130 A / 6,5 kW |
| Tanks | |

Fuel Tank 550 L Aluminium SCR Tank 78 L



| Dimensions (mm) | |
|--|-------|
| Front Overhang | 1500 |
| Wheelbase | 4750 |
| Overall Length | 9830 |
| Distance between 2 nd and 3 th wheel centers | 1320 |
| Overall Cab Length | 2305 |
| Overall Vehicle Height | 3140 |
| Overall Vehicle Width (Excluding Mirrors) | 2540 |
| Chassis Width | 866 |
| Rear Overhang | 2260 |
| Useful Chassis Length | 7190 |
| Chassis Height-Front | 225 |
| Chassis Height-Rear | 285 |
| Ground Clearance - Front | 352 |
| Groung Clearance - Rear | 323 |
| Turning Radius | 10140 |

| Weights (kg) | 1. Axle | 2. Axle | 3. Axle | Total |
|---------------------------------|---------|---------|---------|-------|
| Technically Permissible Weights | 7100 | 12000 | 8700 | 26000 |
| Kerb Weight | 4771 | 1950 | 1452 | 8173 |
| Payload | 2329 | 10050 | 7248 | 17827 |
| GVM (Legal) | 7100 | 11500 | 8700 | 25000 |

STANDART DONANIM

- Air Conditioner
- Radio/CD/MP3 Player
- Auxiliary Cabin Heater (Dry Type)
- Cruise Control
- Disc Brake
- Engine Brake
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Lane Departure Warning System (LDWS)
- Hill Launch Assist
- Differential Lock
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlight Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Manually Operated Sunroof
- Brake Lining Wear Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Rain Sensor
- Auto Light Sensor
- Home Safe Light
- Approach Light
- Front Fog Lamps
- Digital Tachograph
- Spare Wheel
- Tag Axle Lifting (Auto Drop Function)

OPSIYONEL DONANIM

- Firefighter Pack
- Transmission Driven PTO Options & Interior Control Unit
- Engine Driven PTO & Interior Control Unit *
- ADR Pack
- Cold Climate Pack
- Auxiliary Cabin Heater (Wet Type)
- Power Cab Tilting
- Metallic Paint / Special Colors
- 12 R 22,5 Tyre Option
- Low Liner Pack with 315/60 Tyre and 4,11 Axle Ratio
- Advanced Emergency Braking System (AEBS)

^{*} Available for Firefighter Pack Only.